

A FLOW ANALYSIS SYSTEM AND METHOD

Patent number: WO9831989
Publication date: 1998-07-23
Inventor: HILL WAYNE S; BARCK BRUCE N
Applicant: FOSTER MILLER INC (US)
Classification:
- international: G01F1/712; G01N7/00; G01D7/00; G01S15/00
- european: G01F1/66F; G01F1/74; G01N29/036; G01N29/14; G01N29/42; G01N29/44N; G01N29/48
Application number: WO1998US00088 19980102
Priority number(s): US19970784787 19970116


Cited documents:

US5600073
US3392572
US4576036
US4688418
US5390547
more >>

Report a data error here

Abstract of WO9831989

A non-invasive flow analysis system (10) and method wherein a sensor (12), such as an acoustic sensor, is coupled to a conduit (14) for transmitting a signal which varies depending on the characteristics of the flow in the conduit (14). The signal is amplified and there is a filter (24), responsive to the sensor signal, and tuned to pass a narrow band of frequencies proximate the resonant frequency of the sensor. A demodulator (26) generates an amplitude envelope of the filtered signal and a number of flow indicator quantities are calculated based on variations in amplitude of the amplitude envelope. A neural network, or its equivalent, is then used to determine the flow rate in the conduit based on the flow indicator quantities.



Data supplied from the **esp@cenet** database - Worldwide